

FEATURES

- 316L stainless-steel crank handle and axle.
- Commercial crank auto tilt
- 1/2" fiberglass ribs and struts for maximum strength and flexibility.
- 1.5" diameter center pole with a 1/8" aluminum wall thickness provides incredible strength and durability.

ENGINEERED TO WITHSTAND 40 MPH WINDS.

- 4-Layer fabric protection and closed stitching pocket.
- Solid TPU Co-Polymer finial design.
- Stainless-steel hardware throughout.
- Mounting options include permanent, semi-permanent, and freestanding bases for installation on any surface.

FRAME FINISHES







7.5' / 2.3M OCT.



B. clearance: 72" / 182cm

C. closed clearance: 49" / 124cm

D. crank clearance: 36" / 91cm

MAST: 1.5"/38mm WEIGHT: 20 lbs. / 9 kg.



6.5' / 2M SQ.

- A. overall height: 107" / 271cm
- B. clearance: 79" / 200cm
- C. closed clearance: 48" / 121cm
- D. crank clearance: 36" / 91cm

MAST: 1.5"/38mm WEIGHT: 20 lbs. / 9 kg.



FINIAL OPTIONS

Finial color will default to frame finish selection



BF CLASSIC BALL default style



VF VERTEX



9' / 2.7M OCT.

- A. overall height: 107" / 271cm
- clearance: 79" / 200cm
- closed clearance: 48" / 121cm
- D. crank clearance: 36" / 91cm

MAST: 1.5"/38mm WEIGHT: 22 lbs. / 10 kg.



11' / 3.5M OCT.

- A. overall height: 108" / 274cm
- B. clearance: 87" / 220cm
- C. closed clearance: 41" / 104cm
- D. crank clearance: 36" / 91cm

MAST: 1.5"/38m

WEIGHT: 26 lbs. / 26 kg.



7.5' / 2.3M SQ.

- A. overall height: 108" / 274cm
- B. clearance: 87" / 220cm
- C. closed clearance: 41" / 104cm
- D. crank clearance: 36" / 91cm

MAST: 1.5"/38m

WEIGHT: 24 lbs. / 11 kg.

Umbrella clearance dimensions are measured while not mounted in a base. Depending on the selected base, these clearance measurements will change. All dimensions and weights have a +/-5" tolerance based on multiple variables; pin placement height, crank tautness and fabric weight.

Please see our "Umbrella Base Guide by Application" on page 42 for recommended base options, based on the umbrella size and desired application (table use or free-standing).