

FEATURES

- Smooth and effortless pulley system.
- Ergonomically designed ribs maintain the shape and provide added strength.
- 1.5" diameter 1/8" thick aluminum center pole provides incredible strength and durability.

ENGINEERED TO WITHSTAND 35 MPH WINDS.

- Solid marine grade chrome plated aluminum finial.
- Stainless-steel hardware throughout.
- Mounting options include permanent, semi-permanent, and freestanding bases for installation on any surface.

FRAME FINISHES



ANODIZED

FINIAL OPTIONS



BF CHROME CLASSIC BALL



VF CHROME VERTEX default style





845CAM - 7.5' / 2.3M OCT.

A. overall height: 94" / 238cm

B. clearance: 70" / 177cm

C. closed clearance: 44" / 85cm

MAST: 1.5"/38mm WEIGHT: 20 lbs. / 9 kg.

854CAM-9'/2.7M OCT.

A. overall height: 102" / 259cm

B. clearance: 76" / 193cm

C. closed clearance: 42" / 106cm

MAST: 1.5"/38mm WEIGHT: 22 lbs. / 10 kg.

864CAM - 11' / 3.5M OCT.

A. overall height: 108" / 274cm

B. clearance: 82" / 208cm

C. closed clearance: 40" / 101cm

MAST: 1.5"/38mm WEIGHT: 26 lbs. / 12 kg.



454CAM-SQ - 6.5' / 2M SQ.

- A. overall height: 102" / 259cm
- B. clearance: 76" / 193cm
- C. closed clearance: 42" / 106cm

MAST: 1.5"/38mm WEIGHT: 18 lbs. / 8 kg.



864CAM-SQ - 7.5' / 2.3M SQ.

- A. overall height: 108" / 274cm
- B. clearance: 82" / 208cm
- C. closed clearance: 40" / 101cm

MAST: 1.5"/38mm WEIGHT: 24 lbs. / 11 kg.

> Umbrella clearance dimensions are measured while not mounted in a base. Depending on the selected base, these clearance measurements will change. All dimensions and weights have a +/-5" tolerance based on multiple variables; pin placement height, crank tautness and fabric weight.

Please see our "Umbrella Base Guide by Application" on page 42 for recommended base options, based on the umbrella size and desired application (table use or free-standing).